DATASHEET

# EVO6022AP WI-FI 6 ROUTER/MESH





## **Elevated Wi-Fi**

The EVO6022AP, a cutting-edge Wi-Fi 6 AP router and mesh beacon, empowers service providers with a secure, versatile solution for unparalleled Wi-Fi performance. Whether used as a primary AP or mesh extension, its technology ensures seamless coverage and enhanced subscriber satisfaction with innovative software integration.



#### Hardware

Memory: 512MB Flash: 256MB

#### Interfaces

WAN: 1 x 1GE WAN

#### Wi-Fi

Standard: Wi-Fi 6 (802.11 a/b/g/n/ac/ax) Spectral Bands: 2.4GHz (2x2), 802.11ac/ax 5GHz (2x2) Channel Width: 20/40/80/160MHz Throughput: AX3000 3.0 Gbps, 5 GHz: 2402 Mbps (802.11ax), 2.4 GHz: 574 Mbps (802.11ax)

#### **Software Features**

Plume: HomePass, Haystack, Uprise, Harvest OpenSync: OpenSync 4.4, Roadmap to OS6.4 Smart Wi-Fi: Intelligent Mesh, Band / Client Steering Mode: Router or Bridge Mode

### **Physical Specifications**

Operating Temperature: -10°C to 40°C Storage Temperature: -20°C to 50°C Operation Humidity: 10%~80% non-condensing Storage Humidity: 0%~90% non-condensing LED: Network Status Indicator, Wi-Fi Status Indicator, Power Indicator, WPS Status Indicator Buttons: Power ON/OFF, WPS, and Reset Antenna: 5 x 3dBi Internal Antennas Cable: 1M Category 5e RJ45 Cable (x1) Power Supply: 12V/1A



© Evolution Digital, LLC. All Rights Reserved. All values are typical unless noted otherwise. Specifications are subject to change without notification.